NSN 5930-01-464-2095

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-464-2095

Overall Length:
6.500 inches
Overall Height:
7.750 inches
Body Diameter:
7.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.000 inches
Longest Vertical Distance Between Mounting Centers:
3.000 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 130.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
25.00 pounds per square inch gage
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
0.5 amperes inductive load first voltage and 1.0 amperes inductive load first voltage and 1.5 amperes resistive load first voltage and 2.5
amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+2.00/+6.00 actuation point inches of water
Contact Adjustment Type:
External actuation point screw with scale
Contact Voltage Rating In Volts:
24.0 dc at sea level second voltage
Frequency In Hertz:

Gas

60.0 first voltage

Media For Which Designed:

NSN 5930-01-464-2095

Pressure Switch - Page 2 of 2



•	_		
Style	De:	sıar	nator:
,		9.9.	

Cylindrical w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0