

View Online at <https://aerobasegroup.com/nsn/5930-01-464-4488>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

1.130 inches

Body Width:

0.620 inches

Body Height:

0.900 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

277.0 ac

Mounting Surface To Terminal End Distance:

1.060 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

Solder terminals; I192 electrical rating code: 10 amps, 125, 250 and 277 vac; 1/4 hp, 125 vac; 1/2 hp, 250 and 277 vac; 3 amps, 125 vac "I"

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0