

View Online at <https://aerobasegroup.com/nsn/5930-01-464-4529>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

1.320 inches

Overall Height:

2.870 inches

Overall Width:

0.890 inches

Bushing Length:

0.470 inches

Body Length:

1.320 inches

Body Width:

0.890 inches

Body Height:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.245 inches

Actuator Height:

1.050 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

230.0 ac and 250.0 dc

End Application:

Wing tip position and recognition lights on the kdc-10 aircraft

Mounting Surface To Terminal End Distance:

1.350 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

Special Features:

No locking mechanism

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0