

View Online at <https://aerobasegroup.com/nsn/5930-01-467-0109>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.500 inches

Body Length:

0.930 inches

Body Width:

1.300 inches

Body Height:

1.150 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

0.660 inches

Actuator Position-action Relationship:

Center position momentary and center position maintained and right position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 4.000 amperes inductive ac and 2.500 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0