

View Online at <https://aerobasegroup.com/nsn/5930-01-467-0109>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.500 inches

**Body Length:**

0.930 inches

**Body Width:**

1.300 inches

**Body Height:**

1.150 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

0.660 inches

**Actuator Position-action Relationship:**

Center position momentary and center position maintained and right position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

6 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive ac and 4.000 amperes inductive ac and 2.500 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0