

View Online at <https://aerobasegroup.com/nsn/5930-01-468-3241>

Thread Length:

0.292 inches single mounting facility and 0.332 inches single mounting facility

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.667 inches single actuator and 0.707 inches single actuator

Overall Diameter:

Between 0.672 inches and 0.702 inches

Body Thickness:

Between 0.667 inches and 0.791 inches

Individual Section Quantity:

1

End Application:

Ssm-xmitterg

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section periphery

Throw Quantity:

3 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Style Designator:

Switch section, rotary

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0

Mil-std (military Standard):

Mil-dtl-3786 spec.