

View Online at <https://aerobasegroup.com/nsn/5930-01-468-3241>

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Flat Height:**

0.084 inches single actuator and 0.104 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:**

0.667 inches single actuator and 0.707 inches single actuator

**Overall Diameter:**

Between 0.672 inches and 0.702 inches

**Body Thickness:**

Between 0.667 inches and 0.791 inches

**Individual Section Quantity:**

1

**End Application:**

Ssm-xmitterg

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section periphery

**Throw Quantity:**

3 single section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Style Designator:**

Switch section, rotary

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0

**Mil-std (military Standard):**

Mil-dtl-3786 spec.