

View Online at <https://aerobasegroup.com/nsn/5930-01-468-3373>

**Overall Length:**

Between 1.160 inches and 1.260 inches

**Overall Height:**

0.500 inches

**Body Diameter:**

0.640 inches

**Body Height:**

Between 0.280 inches and 0.395 inches

**Distance Between Mounting Facility Centers:**

Between 0.930 inches and 0.944 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 0.930 inches and 0.944 inches

**Shortest Horizontal Distance Between Mounting Centers:**

Between 0.930 inches and 0.944 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

Between 0.930 inches and 0.944 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.930 inches and 0.944 inches

**Shortest Vertical Distance Between Mounting Centers:**

Between 0.930 inches and 0.944 inches

**End Application:**

Sasm-xmitter g

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Facility Circle Radius:**

Between 0.133 inches and 0.147 inches

**Mounting Method:**

Bracket

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage and 1.0 amperes lamp load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

225.00 actuation point degrees fahrenheit and 175.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0