NSN 5930-01-469-7305

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-469-7305

| Hazardous Locations/environmental Protection: |
|---|
| Vibration resistant |
| Overall Length: |
| 3.025 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.500 inches |
| End Application: |
| COMM-OS-UBS-SYTE |
| Flangewidth: |
| 1.438 inches |
| Tempurature Sensing Element Type: |
| Expanding shell |
| Mounting Facility Circle Radius: |
| 0.625 inches |
| Mounting Method: |
| Flange and unthreaded hole |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Three position circular |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 5.01 amperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point not adjustable |
| Contact Stimulus Rating: |
| 140.00 actuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 32.0 dc at sea level second voltage |
| Media For Which Designed: |
| Gas or liquid |
| |
| Style Designator: |
| Style Designator: Cylindrical w/flange |
| |
| Cylindrical w/flange |

--

NSN 5930-01-469-7305

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0