NSN 5930-01-469-7305

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-469-7305

Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
3.025 inches
Unthreaded Mounting Hole Diameter:
0.500 inches
End Application:
COMM-OS-UBS-SYTE
Flangewidth:
1.438 inches
Tempurature Sensing Element Type:
Expanding shell
Mounting Facility Circle Radius:
0.625 inches
Mounting Method:
Flange and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.01 amperes resistive load first voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
140.00 actuation point degrees fahrenheit
Contact Voltage Rating In Volts:
32.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Style Designator: Cylindrical w/flange
Cylindrical w/flange

--

NSN 5930-01-469-7305

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0