

View Online at <https://aerobasegroup.com/nsn/5930-01-469-9694>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.469 inches

**Body Length:**

0.670 inches

**Body Width:**

0.670 inches

**Body Height:**

1.260 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.420 inches and 0.432 inches

**Actuator Height:**

Between 0.936 inches and 1.030 inches

**Actuator Position-action Relationship:**

Center position maintained and up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position locked in and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

1520-01-355-8250

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal and nonturn feature

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes resistive ac and 1.000 amperes inductive dc and 2.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0