

View Online at <https://aerobasegroup.com/nsn/5930-01-470-7437>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.766 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Switch Actuator Quantity:

1

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.396 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.436 inches

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

Hh/mh60 helicopter

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Switch Release Force:

5.0 inch-ounces

Switch Actuating Force:

12.0 inch-ounces

Actuator Movement:

0.012 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Temperature range ambient -65 degrees c to +125 degrees c; dpdt, db

Precious Material And Location:

Contact plating silver and contact plating gold

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0