

View Online at <https://aerobasegroup.com/nsn/5930-01-470-7437>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.766 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Switch Actuator Quantity:**

1

**Actuator Length:**

0.125 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.396 inches

**Actuator Width:**

0.125 inches

**Actuator Free Position Height:**

0.436 inches

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

Hh/mh60 helicopter

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Switch Release Force:**

5.0 inch-ounces

**Switch Actuating Force:**

12.0 inch-ounces

**Actuator Movement:**

0.012 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac

**Special Features:**

Temperature range ambient -65 degrees c to +125 degrees c; dpdt, db

**Precious Material And Location:**

Contact plating silver and contact plating gold

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0