

View Online at <https://aerobasegroup.com/nsn/5930-01-470-9059>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof and moisture resistant and salt spray resistant

**Overall Length:**

Between 1.107 inches and 1.231 inches

**Overall Diameter:**

Between 0.672 inches and 0.702 inches

**Individual Section Quantity:**

3

**End Application:**

5820-01-463-6568

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

36.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 all actuators

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

75.0 milliamperes resistive load ac at sea level

**Contact Arrangement Truth Table:**

Special, 2 pole - 2 positions each section

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0