# NSN 5930-01-471-2659

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-471-2659

# **Body Style:**

Hole mounted

# Center To Center Distance Between Mounting Facilities Parallel To Length:

22.2 millimeters

# Body Length:

39.8 millimeters

#### Body Width:

10.3 millimeters

#### **Body Height:**

15.9 millimeters

#### **Case Material:**

Plastic

# **Unthreaded Mounting Hole Diameter:**

#### 0.31 millimeters

# Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 10.3 millimeters

Actuator Style:

Round

#### Actuator Diameter:

2.8 millimeters

# **Actuator Height:**

2.8 millimeters

# **Actuator Free Position Height:**

5.6 millimeters

# Maximum Voltage Rating In Volts:

250.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

# Pile-up Contact Form Arrangement:

1m single position

# Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

#### Switch Release Force:

50.0 grams

# Switch Actuating Force:

200.0 grams

#### **Actuator Movement:**

1.2 pretravel millimeters and 1.0 overtravel millimeters

# Contact Load Current Rating At Maximum Rated Voltage:

16.000 amperes resistive ac

# NSN 5930-01-471-2659

Sensitive Switch - Page 2 of 2



# Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0