NSN 5930-01-471-7052

Push Switch - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-471-7052

| Thread Class: |
|--|
| 2a |
| Body Diameter: |
| Between 0.870 inches and 0.890 inches |
| Case Material: |
| Plastic |
| Actuator Diameter: |
| Between 0.307 inches and 0.317 inches |
| Actuator Height: |
| Between 0.253 inches and 0.293 inches |
| Actuator Color: |
| Red single actuator |
| Maximum Voltage Rating In Volts: |
| 220.0 ac |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| 52 |
| Contact Load Current Rating At Maximum Rated Voltage: |
| |
| Contact Load Current Rating At Maximum Rated Voltage: |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug Shelf Life: |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: |
| Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive ac Thread Series Designator: Uns Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No |