

View Online at <https://aerobasegroup.com/nsn/5930-01-472-5826>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.469 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Body Height:

0.556 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Left position momentary and right position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.750 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Dielectric withstanding voltage: 1200 v rms at sea-level (center on circuits)

Precious Material And Location:

Terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Specification Data:

96906-ms21357 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0