

View Online at <https://aerobasegroup.com/nsn/5930-01-472-6321>

Thread Class:

3a single threaded hole

Thread Direction:

Right-hand single threaded hole

Overall Length:

2.923 inches

Overall Diameter:

0.091 inches

Distance Between Mounting Facility Centers:

2.932 inches

Pressure Switch Type:

Absolute

Width Across Flats:

0.510 inches

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

18 single threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

4800.00 pounds per square inch gage

Thread Size:

0.5625 inches single threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 microamperes resistive load single voltage and 200.0 microamperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

2350.00 actuation point pounds per square inch gage and 1900.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Special Features:

Operating pressure- 3200 psig; exterior matl shall be stainless steel; elastomeric materials shall be per mil-r-83485

Frequency In Hertz:

5000.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0