

View Online at <https://aerobasegroup.com/nsn/5930-01-473-1030>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

12.70 millimeters

Body Length:

19.80 millimeters

Body Width:

6.40 millimeters

Body Height:

11.20 millimeters

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 2.22 millimeters and 2.29 millimeters

Actuator Length:

3.0 millimeters

Actuator Style:

Rectangular

Actuator Height:

2.36 millimeters

Actuator Width:

3.0 millimeters

Actuator Free Position Height:

8.74 millimeters

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Switch Release Force:

2.2 ounces

Switch Actuating Force:

Between 3.0 ounces and 5.0 ounces

Actuator Movement:

1.27 pretravel millimeters and 0.15 overtravel millimeters and 0.50 differential millimeters

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 23.000 amperes lamp ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0