

View Online at <https://aerobasegroup.com/nsn/5930-01-477-0092>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Splashproof

**Body Diameter:**

0.500 inches

**Bushing Length:**

0.448 inches

**Body Length:**

0.350 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.687 inches

**Actuator Position-action Relationship:**

Left position momentary and right position momentary

**Maximum Voltage Rating In Volts:**

28.0 dc and 250.0 ac

**Mounting Surface To Terminal End Distance:**

0.505 inches

**Inclosure Type:**

Fully enclosed or hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac and 5.000 amperes resistive dc

**Special Features:**

Spdt; satin chrome finish (actuator)

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0