NSN 5930-01-477-9424

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-477-9424

Thread Class:

2a single mounting facility

Thread Length:

 $0.235 \ \text{inches} \ \text{single} \ \text{mounting} \ \text{facility} \ \text{and} \ 0.245 \ \text{inches} \ \ \text{single} \ \text{mounting} \ \text{facility}$

Overall Length:

1.682 inches

First Flat Length:

 $0.705 \ \text{inches} \ \text{single} \ \text{actuator} \ \text{and} \ 0.735 \ \text{inches} \ \text{single} \ \text{actuator}$

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.765 inches single actuator and 0.795 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

28 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

NSN 5930-01-477-9424

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0