## NSN 5930-01-477-9457

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-477-9457

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.235 inches single mounting facility and 0.245 inches single mounting facility

**Overall Length:** 

1.682 inches

First Flat Length:

0.705 inches single actuator and 0.735 inches single actuator

Flat Height:

0.093 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.765 inches single actuator and 0.795 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

1

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

5 single section rear

**Mounting Method:** 

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

28 single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Printed circuit

**Contact Switching Action:** 

Makes before breaks single section rear

**Switch Actuator Positioning Increment:** 

36.0 degrees single actuator

## NSN 5930-01-477-9457

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

200.0 milliamperes resistive load dc at sea level

**Style Designator:** 

Snap or line

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0