

View Online at <https://aerobasegroup.com/nsn/5930-01-477-9467>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.235 inches single mounting facility and 0.245 inches single mounting facility

**Overall Length:**

1.682 inches

**First Flat Length:**

0.705 inches single actuator and 0.735 inches single actuator

**Flat Height:**

0.093 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.765 inches single actuator and 0.795 inches single actuator

**Overall Diameter:**

0.500 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

6 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thready Qty Per Inch (tpi):**

28 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0