NSN 5930-01-478-5494

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-478-5494

Body Style: Bushing/hole mounted Center To Center Distance Between Mounting Facilities Parallel To Length: 0.984 inches Bushing Length: 1.091 inches Body Length: 1.575 inches Body Width: 0.630 inches
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.984 inches Bushing Length: 1.091 inches Body Length: 1.575 inches Body Width: 0.630 inches
0.984 inches Bushing Length: 1.091 inches Body Length: 1.575 inches Body Width: 0.630 inches
Bushing Length: 1.091 inches Body Length: 1.575 inches Body Width: 0.630 inches
1.091 inches Body Length: 1.575 inches Body Width: 0.630 inches
Body Length: 1.575 inches Body Width: 0.630 inches
1.575 inches Body Width: 0.630 inches
Body Width: 0.630 inches
0.630 inches
Dedut Height.
Body Height:
1.732 inches
Unthreaded Mounting Hole Diameter:
0.200 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.674 inches
Actuator Roller Diameter:
0.945 inches
Actuator Roller Width:
0.200 inches
Maximum Voltage Rating In Volts:
125.0 ac or 250.0 ac
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
16.0 ounces
Switch Actuating Force:
42.5 ounces
Actuator Movement:
Between 0.118 overtravel inches and 0.004 differential inches and 0.071 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a

NSN 5930-01-478-5494 Sensitive Switch - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A053a0