

View Online at <https://aerobasegroup.com/nsn/5930-01-478-5494>

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.984 inches

**Bushing Length:**

1.091 inches

**Body Length:**

1.575 inches

**Body Width:**

0.630 inches

**Body Height:**

1.732 inches

**Unthreaded Mounting Hole Diameter:**

0.200 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.674 inches

**Actuator Roller Diameter:**

0.945 inches

**Actuator Roller Width:**

0.200 inches

**Maximum Voltage Rating In Volts:**

125.0 ac or 250.0 ac

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

16.0 ounces

**Switch Actuating Force:**

42.5 ounces

**Actuator Movement:**

Between 0.118 overtravel inches and 0.004 differential inches and 0.071 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0