

View Online at <https://aerobasegroup.com/nsn/5930-01-478-5494>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.984 inches

Bushing Length:

1.091 inches

Body Length:

1.575 inches

Body Width:

0.630 inches

Body Height:

1.732 inches

Unthreaded Mounting Hole Diameter:

0.200 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.674 inches

Actuator Roller Diameter:

0.945 inches

Actuator Roller Width:

0.200 inches

Maximum Voltage Rating In Volts:

125.0 ac or 250.0 ac

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

42.5 ounces

Actuator Movement:

Between 0.118 overtravel inches and 0.004 differential inches and 0.071 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0