

View Online at <https://aerobasegroup.com/nsn/5930-01-478-8656>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.275 inches single mounting facility

**Overall Length:**

2.538 inches

**Flat Height:**

0.217 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.500 inches single actuator

**Overall Diameter:**

1.031 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section rear

**Throw Quantity:**

6 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

2.5 amperes resistive load ac at sea level

**Special Features:**

Epoxy seal terminals

**Precious Material And Location:**

Contacts gold and cocontacts silver

**Precious Material:**

Gold and silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0