

View Online at <https://aerobasegroup.com/nsn/5930-01-482-5104>

Overall Length:

85.0 millimeters

Overall Height:

75.0 millimeters

Overall Width:

30.0 millimeters

Body Length:

70.0 millimeters

Body Height:

30.0 millimeters

Unthreaded Mounting Hole Diameter:

5.2 millimeters

Distance Between Mounting Facility Centers:

20.0 millimeters

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -10.0 degrees fahrenheit and 175.0 degrees fahrenheit

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

5800.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+360.00/+3600.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point hex nut

Pressure Connector Type:

Swivel nut, compression, threaded internal single connection

Special Features:

Pressure inlet thread is 0.250 in. Npt; fluid temperature rating is minus 10.0 to plus 210.0 deg. F; viscosity is 220.0 ssu.; switching rate is 100.0 cycles per minute; housing material aluminum; piston material stainless steel; seal material buna-n

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0