## NSN 5930-01-482-5104



Pressure Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-482-5104 **Overall Length:** 85.0 millimeters **Overall Height:** 75.0 millimeters Overall Width: 30.0 millimeters **Body Length:** 70.0 millimeters **Body Height:** 30.0 millimeters **Unthreaded Mounting Hole Diameter:** 5.2 millimeters **Distance Between Mounting Facility Centers:** 20.0 millimeters **Pressure Switch Type:** Differential **Operating Tempurature Rating:** Between -10.0 degrees fahrenheit and 175.0 degrees fahrenheit **Mounting Method:** Base and unthreaded hole **Contact Action Stimulus:** Increase **Proof Pressure:** 5800.00 pounds per square inch **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, double throw, three positions maintained **Contact Adjustability:** Actuation point adjustable **Contact Adjustment Range:** +360.00/+3600.00 actuation point pounds per square inch **Contact Adjustment Type:** External actuation point hex nut **Pressure Connector Type:** Swivel nut, compression, threaded internal single connection **Special Features:** Pressure inlet thread is 0.250 in. Npt; fluid temperature rating is minus 10.0 to plus 210.0 deg. F; viscosity is 220.0 ssu.; switching rate is 100.0 cycles per minute; housing material aluminum; piston material stainless steel; seal material buna-n Media For Which Designed:

Rectangular

**Style Designator:** 

Liquid

## NSN 5930-01-482-5104

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0