

View Online at <https://aerobasegroup.com/nsn/5930-01-482-8602>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.326 inches

Overall Diameter:

Between 0.495 inches and 0.515 inches

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

Aircraft, awacs, e-3a

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

10 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

28 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Special Features:

Closed construction, flux seal, low level capability, no shaft grouding

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Specification Data:

81349-mil-s-3786/20h government specification

Specification Or Standard:

K type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0