

View Online at <https://aerobasegroup.com/nsn/5930-01-483-8753>

Overall Length:

6.500 inches

Overall Height:

7.750 inches

Body Diameter:

7.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.000 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

25.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

0.5 amperes inductive load first voltage and 1.0 amperes inductive load first voltage and 1.5 amperes resistive load first voltage and 2.5 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+1.00/+4.00 actuation point inches of water

Contact Adjustment Type:

External actuation point screw with scale

Contact Voltage Rating In Volts:

24.0 dc at sea level second voltage

Special Features:

Manufacturers item name: floating contact null switch for high and low actuation; adjustable null span set: 0.03; adjustable null span set: 0.12

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0