

View Online at <https://aerobasegroup.com/nsn/5930-01-483-8753>

**Overall Length:**

6.500 inches

**Overall Height:**

7.750 inches

**Body Diameter:**

7.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 130.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

25.00 pounds per square inch gage

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

0.5 amperes inductive load first voltage and 1.0 amperes inductive load first voltage and 1.5 amperes resistive load first voltage and 2.5 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+1.00/+4.00 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw with scale

**Contact Voltage Rating In Volts:**

24.0 dc at sea level second voltage

**Special Features:**

Manufacturers item name: floating contact null switch for high and low actuation; adjustable null span set: 0.03; adjustable null span set: 0.12

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0