## NSN 5930-01-484-8018

Pressure Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-484-8018
Hazardous Locations/environmental Protection:
Weathertight
Pressure Switch Type:
Differential
Contact Action Stimulus:
Increase
Proof Pressure:
1000.00 pounds per square inch
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point adjustable
Contact Voltage Rating In Volts:
250.0 ac at sea level single voltage
Special Features:
Spdt; 9/16-18 sae straight thread process connections; aluminum housing
Media For Which Designed:
Liquid or gas
Style Designator:
Style Designator.
Cylindrical w/port
Cylindrical w/port
Cylindrical w/port Shelf Life:
Cylindrical w/port Shelf Life: N/a
Cylindrical w/port Shelf Life: N/a
Cylindrical w/port Shelf Life: N/a Unit Of Measure:
Cylindrical w/port Shelf Life: N/a Unit Of Measure:  Demilitarization:
Cylindrical w/port Shelf Life: N/a Unit Of Measure:  Demilitarization: No
Cylindrical w/port Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Cylindrical w/port Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Cylindrical w/port Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Cylindrical w/port Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Cylindrical w/port Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: