NSN 5930-01-488-6687

Thermostatic Switch - Page 1 of 1

A048b0



View Online at https://aerobasegroup.com/nsn/5930-01-488-6687

| Hazardous Locations/environmental Protection: |
|--|
| Humidity resistant and vibration resistant |
| Overall Length: |
| 32.0 millimeters |
| Overall Height: |
| 12.0 millimeters |
| Body Diameter: |
| 16.0 millimeters |
| Distance Between Mounting Facility Centers: |
| 24.0 millimeters |
| Tempurature Sensing Element Type: |
| Disc |
| Operating Tempurature Rating: |
| Between 65.0 degrees celsius and 85.0 degrees celsius |
| Mounting Method: |
| Bracket |
| Features Provided: |
| Automatic reset |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Terminal Type: |
| Quick disconnect, male |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level second voltage |
| Special Features: |
| Important - when ordering must specify operating temperature range - open 80 deg. C. Plus or minus 5 deg. C close 70 deg. C. Plus or |
| minus 5 deg. C; part name assigned by controlling agency - bimetallic disc thermostat; shock resistant; single pole double throw; normally |
| closed; open on rise; contact point 1 to 100 milliamps; phenolic body; aluminum open cap; stainless steel adjustable mounting bracket |
| Media For Which Designed: |
| Gas |
| Style Designator: |
| Disc w/flange |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |