

View Online at <https://aerobasegroup.com/nsn/5930-01-491-9487>

Thread Class:

2a single threaded bushing

Overall Length:

3.610 inches

Outside Diameter:

0.750 inches single connection

Body Length:

2.860 inches

Overall Diameter:

0.750 inches

End Application:

Nsn 2350-01-390-4683 recovery vehicle, full tracked

Pressure Switch Type:

Gage

Width Across Flats:

0.938 inches

Operating Temperature Rating:

Between -25.0 degrees fahrenheit and 120.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

0.5 amperes lamp load single voltage and 1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

45.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

Special Features:

Spdt; snap-acting; sealed from environment-water, sand and dirt; material - 303 series stainless steel and aluminum alloy, anodized; seals-mitrite; lubrication-silicone base; receptacle and port shall be supplied with protective caps

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0