NSN 5930-01-492-3606

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-492-3606

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Height: |
| 1.4375 inches |
| Overall Diameter: |
| 1.3125 inches |
| Individual Section Quantity: |
| 2 |
| End Application: |
| B-2 bomber (atb) aircraft |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 2 single section rear |
| Throw Quantity: |
| 2 single section rear |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thread Size: |
| 0.375 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 11 single actuator |
| 11 Single detactor |
| Terminal Type: |
| - |
| Terminal Type: |
| Terminal Type: Tab, solder lug |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver Precious Material: Silver |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver Precious Material: |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver Precious Material: Silver Style Designator: Circular wafer, bushing mount |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver Precious Material: Silver Style Designator: Circular wafer, bushing mount Thread Series Designator: |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver Precious Material: Silver Style Designator: Circular wafer, bushing mount |
| Terminal Type: Tab, solder lug Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 1.5 amperes resistive load dc at sea level Precious Material And Location: Clips and rotors silver Precious Material: Silver Style Designator: Circular wafer, bushing mount Thread Series Designator: |

NSN 5930-01-492-3606Rotary Switch - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

Demilitarization:

No

Fiig:

A052b0