NSN 5930-01-492-9063

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-492-9063

Overall Length:
4.000 inches
Overall Height:
9.687 inches
Overall Width:
2.343 inches
Body Length:
3.562 inches
Body Height:
4.218 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Mounting Facility Centers:
2.750 inches
Capillary Tube Length:
72.0 inches
Bulb Length:
3.125 inches
Bulb Diameter:
0.375 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load third voltage
Contact Adjustability:
Deactuation point not adjustable
Contact Adjustment Range:
+50.00/+650.00 actuation point pounds per square inch and +50.00/+650.00 deactuation point pounds per square inch
Contact Adjustment Type:
External actuation point screw

1.00 actuation point degrees fahrenheit

Contact Stimulus Rating:

NSN 5930-01-492-9063

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 480.0 ac at sea level third voltage Special Features: 100 series tempeture switch Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid Style Designator: Rectangular Shelf Life: N/a Unit Of Measure:

No

Fiig:

A048b0

Demilitarization: