

View Online at <https://aerobasegroup.com/nsn/5930-01-493-3201>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Body Width:

0.688 inches

Body Height:

0.437 inches

Case Material:

Metal

Switch Actuator Quantity:

1

Actuator Length:

0.530 inches

Actuator Style:

Rectangular

Actuator Height:

0.110 inches

Actuator Width:

0.297 inches

Actuator Color:

Black, opaque single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

A/a single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 250.0 ac and 28.0 dc

End Application:

F15e-saip

Mounting Surface To Terminal End Distance:

1.650 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 4.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

Special Features:

Nvis compatible lighting; emi/rfi shielding; average brightness in foot lamberts-150; replaceable lamps; operating temperature- minus 55 degrees c to 85 degrees c

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0