

View Online at <https://aerobasegroup.com/nsn/5930-01-493-4231>

**Thread Class:**

2a single threaded bushing

**Overall Length:**

3.610 inches

**Outside Diameter:**

0.750 inches single connection

**Body Length:**

2.860 inches

**Overall Diameter:**

0.750 inches

**End Application:**

Nsn 2350-01-390-4683 recovery vehicle, full tracked

**Pressure Switch Type:**

Gage

**Width Across Flats:**

0.938 inches

**Operating Temperature Rating:**

Between -25.0 degrees fahrenheit and 120.0 degrees fahrenheit

**Mounting Method:**

Threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.438 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

0.5 amperes lamp load single voltage and 1.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

300.00 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Gasket seal, threaded external single connection

**Special Features:**

Ysptd; snap-acting; sealed from environment-water, sand and dirt; material-303 series stainless steel and aluminum alloy, anodized; seals-nitrite; lubrication-silicone base; receptacle and port shall be supplied with protective caps

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0