

View Online at <https://aerobasegroup.com/nsn/5930-01-493-7958>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

20.000 inches

**Body Length:**

1.380 inches

**Overall Diameter:**

1.060 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -20.0 degrees fahrenheit and 150.0 degrees fahrenheit

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

375.00 actuation point pounds per square inch gage and 275.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

240.0 ac at sea level single voltage

**Pressure Connector Type:**

Swivel nut, flare, threaded internal single connection

**Special Features:**

Ul sa512 and csa lr 1942 listed; sae female flare fitting with valve core depressor; operating temperature refrigerant -35 degrees f to +275 degrees f; 18 inches long 18 awg leads

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0