## NSN 5930-01-493-9130

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-493-9130 **Inside Diameter:** 0.250 inches single connection **Overall Length:** 8.000 inches **Body Length:** 3.000 inches **Overall Diameter:** 0.870 inches **End Application:** AIRC-ON-DIT-IONE **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -40.0 degrees celsius and 125.0 degrees celsius **Contact Action Stimulus:** Decrease **Proof Pressure:** 500.00 pounds per square inch gage **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Wire lead **Contact Load Current Rating:** 5.0 milliamperes resistive load single voltage and 2.0 amperes resistive load single voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 3.00 actuation point pounds per square inch and 6.00 deactuation point pounds per square inch **Contact Voltage Rating In Volts:** 9.0 dc at sea level first voltage **Pressure Connector Type:** Swivel nut, flare, threaded internal single connection **Special Features:** Refrigerant operating temperature -60 degrees c to +135 degrees c; life under miliamp load 1, 000, 000 cycles; resistance to vibration 20 gram from 50 to 200 hz, 8 hours in x-y-z direction Media For Which Designed: Gas or liquid **Style Designator:** Cylindrical Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5930-01-493-9130

Pressure Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0