

View Online at <https://aerobasegroup.com/nsn/5930-01-496-7684>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.060 inches

Overall Height:

7.500 inches

Overall Width:

5.500 inches

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

6

End Application:

Radar set an/tpn31 5840014508126

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section front

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

Special Features:

Contacts moveable phosphor bronze, stationary copper; insulation resistnace 200 megaohms, 12 ea studs, frt mounted back stud connected

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0