

View Online at <https://aerobasegroup.com/nsn/5930-01-497-0403>

**Thread Class:**

3a

**Body Style:**

Bushing mount

**Body Diameter:**

Between 0.583 inches and 0.585 inches

**Bushing Length:**

Between 0.320 inches and 0.620 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Position-action Relationship:**

Center position maintained and left position momentary and right position maintained

**Maximum Voltage Rating In Volts:**

125.0 dc

**End Application:**

Torpedo tube bank support module assembly; los angeles cla

**Mounting Surface To Terminal End Distance:**

Between 1.275 inches and 1.285 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, both positions maintained 1st switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc

**Special Features:**

2 pole, 3 position, min.28vdc

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 pin

**Specification Data:**

81349-mil-s-83731 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0