

View Online at <https://aerobasegroup.com/nsn/5930-01-497-0403>

Thread Class:

3a

Body Style:

Bushing mount

Body Diameter:

Between 0.583 inches and 0.585 inches

Bushing Length:

Between 0.320 inches and 0.620 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Position-action Relationship:

Center position maintained and left position momentary and right position maintained

Maximum Voltage Rating In Volts:

125.0 dc

End Application:

Torpedo tube bank support module assembly; los angeles cla

Mounting Surface To Terminal End Distance:

Between 1.275 inches and 1.285 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained 1st switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

2 pole, 3 position, min.28vdc

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 pin

Specification Data:

81349-mil-s-83731 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0