

View Online at <https://aerobasegroup.com/nsn/5930-01-497-6812>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.950 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Height:

1.275 inches

Overall Width:

0.700 inches

Body Length:

1.950 inches

Body Width:

0.700 inches

Body Height:

0.920 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.112 inches

Actuator Free Position Height:

Between 0.600 inches and 0.630 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

0.085 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0