

View Online at <https://aerobasegroup.com/nsn/5930-01-499-5092>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.750 inches

Outside Diameter:

1.000 inches single connection

Body Length:

2.800 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Width Across Flats:

1.185 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Clamp

Features Provided:

Electrical box connector

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage and 400.0 milliamperes lamp load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2400.00 actuation point pounds per square inch and 2000.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0