## NSN 5930-01-499-9299

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-499-9299

В	ody Style:
Но	ble mounted
Ce	enter To Center Distance Between Mounting Facilities Parallel To Length:
19	0.3 millimeters
В	ody Length:
Be	etween 74.4 millimeters and 76.0 millimeters
В	ody Width:
Be	etween 25.1 millimeters and 25.7 millimeters
В	ody Height:
44	.0 millimeters
Ac	ctuator Style:
Fle	exible
Ac	ctuator Diameter:
6.	5 millimeters
Ac	ctuator Height:
13	30.0 millimeters
Ma	aximum Voltage Rating In Volts:
48	30.0 ac and 250.0 dc
Er	nd Application:
49	040-01-445-0086
In	closure Type:
Fι	Illy enclosed
M	ounting Method:
Sc	crew
Sv	witch Release Force:
14	9.0 grams
Sv	vitch Actuating Force:
15	i0.0 grams
Ac	ctuator Movement:
15	i.0 pretravel degrees
Co	ontact Load Current Rating At Maximum Rated Voltage:
15	0.000 amperes resistive ac and 15.000 amperes inductive ac and 3.000 amperes lamp ac and 5.000 amperes motor ac
Те	erminal Type And Quantity:
2 :	socket, integrated wire termination
Sł	nelf Life:
N/	a
Ur	nit Of Measure:
De	emilitarization:
No	
Fi	ig:
AC	053a0