

View Online at <https://aerobasegroup.com/nsn/5930-01-500-4004>

Thread Class:

2a single mounting facility

Overall Length:

Between 1.202 inches and 1.332 inches

Overall Diameter:

Between 0.485 inches and 0.515 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

12 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

28 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Special Features:

Pre-set stops - rotational limits counter-clockwise position 4 and clockwise is position 6; available positions are 4, 5, and 6

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0