

View Online at <https://aerobasegroup.com/nsn/5930-01-501-6624>

**Hazardous Locations/environmental Protection:**

Oiltight and dusttight

**Overall Length:**

2.810 inches

**Overall Height:**

5.750 inches

**Overall Width:**

2.370 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.720 inches

**Longest Vertical Distance Between Mounting Centers:**

2.720 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port and tamper proof cap

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

3000.00 pounds per square inch gage

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

7.5 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+30.00/+200.00 actuation point pounds per square inch gage and +20.00/+170.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0