

View Online at <https://aerobasegroup.com/nsn/5930-01-503-1487>

Overall Length:

Between 3.370 inches and 3.430 inches

Overall Height:

Between 2.225 inches and 2.245 inches

Overall Width:

Between 1.929 inches and 1.949 inches

Unthreaded Mounting Hole Diameter:

0.140 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.780 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.200 inches single mounting facility

Operating Temperature Range:

-65.0/+085.0 degrees celsius

End Application:

An/spn-35c

Mounting Method:

Unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Contact Load Current Rating:

120.0 milliamperes resistive load ac at sea level and 120.0 milliamperes resistive load ac at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

Contact Arrangement Truth Table:

Bcd, separate common to not-true bits, 2 pole - 10 positions single section

Product Name:

Digital switch assembly

Special Features:

Assembly includes one spacer, marked .400 wdt; 2 modules; 1 modules (stops @ 0 and 2); 4 screws, 2-56 x 1/4 inch, pph; 2 studs; one rh end bracket; 1 lh end bracket

Color:

White each indicator marking

Precious Material And Location:

Printed circuit card gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0